


CARNES COMPANY, 448 S. Main St., P. O. Box 930040, Verona, WI 53593-0040 Phone: (608)845-6411 Fax: (608)845-6504 carnes@carnes.com



Section View

#### Model FLDC

#### Standard Specifications

**Frame:** .081 extruded aluminum, 4-1/8" deep

**Blades:** .081 extruded aluminum positioned on a 40° angle on approximately 4.625" centers

**Finish:** mill aluminum (standard)

**Screen:** 3/4" x .051" flattened aluminum in removable frame. Screen is mounted as standard on inside (rear) as looking from exterior of building.


**Maximum Panel Size:** 120"w x 84"h or 84"w x 120"h

**Minimum Panel Size:** 12"w x 12"h


#### Options (at additional cost)

- Filter Racks
- Security Bars
- Special Shapes
- Variety of Screens
- Sub-Frames
- Selection of finishes; prime coat, kynar, baked enamel, clear and color anodize, epoxy and heresite


Consult Carnes for other special requirements.



Flanged Frame  
Optional



Extended Sill  
Optional



\*Width and height dimensions are approximately 1/4" under listed size.

Tag	Qty.	Size		Frame	Variations
		Width	Height		

**Project**  
**Arch./Engr.**  
**Representative**

**Location**  
**Contractor**  
**Date**

## Free Area in Square Feet


HEIGHT INCHES	WIDTH IN INCHES																		
	12	18	24	30	36	42	48	54	60	66	72	78	84	90	96	102	108	114	120
12	0.19	0.31	0.43	0.54	0.66	0.78	0.89	1.01	1.13	1.24	1.36	1.48	1.59	1.71	1.83	1.94	2.06	2.18	2.29
18	0.50	0.80	1.10	1.41	1.71	2.01	2.31	2.62	2.92	3.22	3.53	3.83	4.13	4.43	4.74	5.04	5.34	5.65	5.95
24	0.77	1.23	1.70	2.16	2.63	3.09	3.56	4.02	4.49	4.96	5.42	5.89	6.35	6.82	7.28	7.75	8.21	8.68	9.14
30	0.96	1.54	2.13	2.71	3.30	3.88	4.46	5.05	5.63	6.22	6.80	7.38	7.97	8.55	9.13	9.72	10.30	10.89	11.47
36	1.15	1.85	2.55	3.25	3.96	4.66	5.36	6.06	6.76	7.46	8.16	8.86	9.56	10.26	10.96	11.66	12.36	13.06	13.76
42	1.43	2.29	3.16	4.02	4.89	5.76	6.62	7.49	8.36	9.22	10.09	10.95	11.82	12.69	13.55	14.42	15.29	16.15	17.02
48	1.61	2.59	3.57	4.55	5.53	6.51	7.49	8.47	9.45	10.43	11.41	12.39	13.37	14.35	15.33	16.31	17.29	18.27	19.25
54	1.92	3.09	4.26	5.42	6.59	7.76	8.93	10.10	11.26	12.43	13.60	14.77	15.93	17.10	18.27	19.44	20.61	21.77	22.94
60	2.11	3.40	4.68	5.97	7.25	8.54	9.82	11.11	12.39	13.67	14.96	16.24	17.53	18.81	20.10	21.38	22.67	23.95	25.23
66	2.35	3.78	5.21	6.64	8.07	9.50	10.93	12.36	13.79	15.22	16.65	18.08	19.51	20.94	22.37	23.80	25.23	26.66	28.09
72	2.81	4.52	6.23	7.94	9.65	11.36	13.07	14.78	16.49	18.20	19.90	21.61	23.32	25.03	26.74	28.45	30.16	31.87	33.58
78	2.88	4.63	6.39	8.14	9.89	11.64	13.39	15.14	16.90	18.65	20.40	22.15	23.90	25.65	27.40	29.16	30.91	32.66	34.41
84	3.07	4.94	6.81	8.68	10.55	12.42	14.28	16.15	18.02	19.89	21.76	23.63	25.49	27.36	29.23	31.10	32.97	34.84	36.70
90	3.28	5.27	7.27	9.26	11.25	13.25	15.24	17.23	19.23	21.22	23.21	25.21	27.20	29.19	31.18	33.18	35.17	37.16	39.16
96	3.55	5.70	7.86	10.02	12.17	14.33	16.48	18.64	20.80	22.95	25.11	27.26	29.42	31.57	33.73	35.89	38.04	40.20	42.35
102	3.82	6.13	8.45	10.77	13.09	15.41	17.73	20.05	22.36	24.68	27.00	29.32	31.64	33.96	36.28	38.59	40.91	43.23	45.55
108	3.96	6.37	8.78	11.19	13.60	16.01	18.42	20.82	23.23	25.64	28.05	30.46	32.87	35.28	37.68	40.09	42.50	44.91	47.32
114	4.24	6.81	9.38	11.96	14.53	17.10	19.68	22.25	24.82	27.40	29.97	32.54	35.12	37.69	40.26	42.84	45.41	47.98	50.56
120	4.28	6.89	9.49	12.09	14.69	17.30	19.90	22.50	25.10	27.71	30.31	32.91	35.51	38.12	40.72	43.32	45.92	48.53	51.13

Beginning point of WATER PENETRATION is 812 fpm  
free area velocity at .01 oz. of water penetration

## Water Penetration


Standard Air - .075lb/ft<sup>3</sup>

## Pressure Drop



### FREE AREA VELOCITY (FT/MIN)

Standard air - .075 lbs per cu ft  
Ratings do not include the effect of a wire birdscreen  
Test based on a 48" x 48" test size, 15 min test duration



The Carnes Company certifies that the model FLDC/FKDC louver shown herein is licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 511 and comply with the requirements of the AMCA Certified Ratings Program. The AMCA Certified Ratings Seal applies to air performance ratings and water penetration ratings.